

# **DECLARATION OF PERFORMANCE**

According to Regulation (EU) Nr. 305/2011 of 9th March 2011 Nr. **DoP\_WWS\_2023\_04\_SP** 

1. Unique identification code of the product-type:

#### **STRUCTA**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

# STRUCTA and fittings

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

# Short fibre-cement profiled sheets and fittings for roof cladding according to EN494:2012+A1:2015

 Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
 Producer:

# SWISSPEARL GROUP AG Eternitstrasse 3 CH 8867 Niederurnen Switzerland

Production plants:

## Swisspearl Slovenija d.o.o., Deskle, Slovenia

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)::

#### Not-applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

#### System 3

7. Notified bodies for type tests:

ZAG - ZAVOD ZA GRADBENISTVO SLOVENIJE (Notified body: 1404),

Notified bodies for fire tests:

ZAG - ZAVOD ZA GRADBENISTVO SLOVENIJE (Notified body: 1404)

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

# Not-applicable



#### 9. Declared performance :

Essential characteristics	Performance	Harmonised technical specification
Туре	NT	
Mechanical resistance	Class C	
Density	≥ 1.6 g·cm <sup>-3</sup>	
Reaction to fire <sup>a</sup>	A2-s1, d0	
Water impermeability	No water drops	
Dimensional stability <sup>a</sup>	Panels  Length +3 / -5 mm  Width ± 5 mm  Thickness +0,5 / 0,3 mm  Fittings  Length and Width ± 10 mm  Thickness ± 1mm	EN 494:2012+A1:2015
Release of dangerous substances <sup>a</sup>	No performance declared (NPD)	
Durability against		
- warm water	R <sub>L</sub> ≥ 0.7	
- wet-dry	R <sub>L</sub> ≥ 0.7	
- freeze-thaw	R <sub>L</sub> ≥ 0.7	
- heat-rain	Fulfilled	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

**Esben Moos** 

Head of Product Compliance & Application

Engineering

Swisspearl Group AG

Niederurnen, 01.04.2023

Joachim Ebenhoch

**Head of Group Product Management** 

Swisspearl Group AG

Niederurnen, 01.04.2023