

## DECLARATION OF PERFORMANCE

According to Regulation (EU) Nr. 305/2011 of 9<sup>th</sup> March 2011  
Nr. DoP\_PGR\_2023\_04\_SP

1. Unique identification code of the product-type:

**SWISSPEARL®Largo Panels**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**SWISSPEARL®Largo Panels**

**Product family: Gravial**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Fibre-cement flat sheets for internal and external applications and cladding according to EN12467:2012+A2:2018**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):  
Producer:

**SWISSPEARL GROUP AG  
Eternitstrasse 3  
CH 8867 Niederurnen  
Switzerland**

Production plant:

**Swisspearl Schweiz AG, Niederurnen, Switzerland**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**Not-applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

7. Notified bodies for type tests:

**Materialprüfanstalt für das Bauwesen und Produktionstechnik Hannover (Notified Body: 0764)**

Notified bodies for fire tests:

**Materialprüfungsamt Nordrhein-Westfalen (Notified Body: 0432)**

Institute for test of release of dangerous substances:

**ALAB – Analyse Labor in Berlin GmbH**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued

**Not-applicable**

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Type	NT	EN12467:2012+A2:2018
Mechanical resistance	Class A4	
Reaction to fire	A2-s1, d0	
Release of dangerous substances	No performance declared (NPD)	
Water impermeability	No water drops	
Resistance against <ul style="list-style-type: none"> <li>- warm water</li> <li>- dry-wet</li> <li>- freeze-thaw</li> <li>- heat-rain</li> </ul>	<ul style="list-style-type: none"> <li>R<sub>L</sub> ≥ 0.75</li> <li>R<sub>L</sub> ≥ 0.75</li> <li>R<sub>L</sub> ≥ 0.75</li> <li>Fulfilled</li> </ul>	
Dimensional stability	Level I for edged Panels Level II for unedged Panels	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



**Esben Moos**

Head of Product Compliance & Application  
Engineering  
Swisspearl Group AG  
Niederurnen, 01.04.2023



**Joachim Ebenhoch**

Head of Group Product Management  
Swisspearl Group AG  
Niederurnen, 01.04.2023