SШISSPEARL

Declaration of Performance No. 024/DoP

In accordance with Regulation (EU) No 305/2011 of the European Parliament and of the Council laying down harmonised conditions for the marketing of construction products (CPR EU 305/2011)

1. Unique identification code of the product-type:

Fibre-cement profiled sheets and fittings

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Swisspearl W146-8 RC Profile 146,5 mm/48 mm, Thickness 6 mm (B6 RC, B6-S, Cemsix, Cembonit B6S, Cemscape)

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Roofing Internal wall finishes External wall and ceiling finishes

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Swisspearl Group AG Eternitstrasse 3 CH-8865 Niederurnen Switzerland Email: <u>info@swisspearl.com</u>

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

AVCP System 3

SШISSPEARL

6a. Name and identification number of the notified body (in case of the declaration of performance concerning a construction product covered by a harmonised standard):

Technical and Testing Institute of Construction Prague, s. p. Notified body No. 1020 Branch 0700– Ostrava, U Studia 14 700 30, Ostrava-Zábřeh, Czech Republic

Notified Body performed Initial Type Test under system 3 according to EN 494. Issued protocol on the initial type test no. 1020-CPD-070030730 as of 8th February 2007 and report no.1020-CPD-070030736 as of 8th February 2007.

PAVUS, a.s. Notified body No. 1391 Prosecká 412/74, 190 00 PRAHA 9 – Prosek, Czech Republic

Notified Body performed reaction to fire testing and classification according EN 13501-1. Classification report no. PK1-01-07-009-E-1 (colored variants), dated December 8th, 2016.

6b. Name and identification number of the Technical Assessment Body (in case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued):

Not applicable

Fibre-cement profiled sheets – NT, profile 146 mm / 48 mm, thickness 6 mm		
Essential characteristics	Performance	Harmonised technical specification
Type of sheets	NT	
Mechanical resistance	CIX]
Breaking load	Min. 4250 N/m	
Bending moment	Min. 55 Nm/m	
Apparent density	min 1 600 kg/m ³]
Impact resistance	Pass]
External fire performance	BROOF (deemed to satisfy)]
Reaction to fire	A2-s1, d0	
Water impermeability	No water drops	EN 494:2012+A1:2015
Dimensional variations		Fibre-cement profiled
Length	± 10 mm	sheets and fittings
Width	+ 10 mm / - 5 mm	Product specification
Thickness	6,0 mm ± 0,6 mm	and test methods
Height of the corrugations	48 mm ± 3 mm	
Pitch	146,5 ± 2 mm	
Squareness	max 6 mm/m	4
Release of dangerous substance	No performance determined	4
Durability against warm water	R _L ≥ 0,7	1
Durability against soak/dry	R _L ≥ 0,7	_
Durability against freeze-thaw	R∟ ≥ 0,7	
Durability against heat-rain	Pass	

7. Declared performance:

SШISSPEARL

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

EN 494:2012+A1:2015 Fibre-cement profiled sheets and fittings Product specification and test methods

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Esben Moos, Group Technical Manager Aalborg, March 23rd, 2023

Ese 40