

# **Declaration of Performance**No. 018/DoP

In accordance with Regulation (EU) No 305/2011 of the European Parliament and of the Council laying down harmonised conditions for the marketing of construction products (CPR EU 305/2011)

1. Unique identification code of the product-type:

#### Fibre-cement slates

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

## **Swisspearl Slates**

(Textured Straight 200x200, Textured Straight 300x300, Německý čtverec, Česká šablona, Dánský obdélník, Anglický obdélník, Bobrovka, Betternit, Dominant, Horal, Rhombus, Rhombus šablona, Berona, Jutland, Zeeland, Moorland, Westerland, Diamond Slate, Skifre 40/40, Skifre 30/60, Skifre 60/60, Dolmen, Bravan, Cembrit Quadra)

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Roofing (roof coverings)
Cladding
Internal and external wall finishes

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Swisspearl Group AG
Eternitstrasse 3
CH-8867 Niederurnen, Switzerland
Email: info@swisspearl.com

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

## Not applicable

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

AVCP System 3 / System 4



6a. Name and identification number of the notified body (in case of the declaration of performance concerning a construction product covered by a harmonised standard):

## For products manufactured according to system 3

Technical and Testing Institute of Construction Prague, s. p., Notified body No. 1020
Branch 0700– Ostrava, U Studia 14, 700 30, Ostrava-Zábřeh, Czech Republic

Notified Body performed the Initial Type Test according to EN 492.

PAVUS, a.s. Notified body No. 1391 Prosecká 412/74, 190 00 PRAHA 9 Prosek, Czech Republic

Notified Body performed reaction to fire and classification according to EN 13501-1.

## For products manufactured according to system 4

Manufacturer performed the Initial Type Test according to EN 492.

IBS – Institut für Brandschutztechnik und Sicherheitsforschung GmbH Notified body No. 1322 Petzoldstrasse 45 4020 Linz, Austria

Notified Body performed reaction to fire and classification according to EN 13501-1.

6b. Name and identification number of the Technical Assessment Body (in case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued):

Not applicable



## 7. Declared performance:

Essential characteristics	Performance		Harmonised technical specification
Type of sheets	NT		
Mechanical resistance	h/mm	Bending moment	
	h ≤ 350	30 Nm/m	
	350 < h < 450	40 Nm/m	
	450 < h < 600		
	600 < h < 850	55 Nm/m	
Apparent density	Min. 1 600 kg/m <sup>3</sup>		
External fire performance	B <sub>ROOF</sub> (deemed to satisfy)		EN 492:2012+A2:2018
Reaction to fire	4 mm slates	A1	Fibre-cement slates and
	5.2 mm slates	A2-s1, d0	fittings - Product
Water impermeability	No water drops		specification
Dimensional variations			and test methods
Length, width	± 3 mm		
Thickness	+25% / -10% nominal value		
Release of dangerous substance	No performance determined		
Durability against warm water	R <sub>L</sub> ≥ 0,75		
Durability against soak/dry	R <sub>L</sub> ≥ 0,75		
Durability against freeze-thaw	R <sub>L</sub> ≥ 0,75		
Durability against heat-rain	Pass		

Fibre-cement fittings – NT, thickness 6 mm or 4 mm					
Essential characteristics	Performance		Harmonised technical specification		
Type of sheets	NT				
Apparent density	min 1 300 kg/m <sup>3</sup>				
Reaction to fire	Unpainted fittings	A1	EN 400,0040 ( A 0,0040		
	Painted fittings	A2-s1, d0	EN 492:2012+A2:2018 Fibre-cement slates and		
Dimensional variations			fittings - Product specification		
Length	± 10 mm		and test methods		
Width	± 10 mm		and test methods		
Thickness	± 1 mm				
Release of dangerous substance	No performance determined				
Durability against freeze-thaw	Pass				



8. Appropriate Technical Documentation and/or Specific Technical Documentation:

EN 492:2012+A2:2018
Fibre-cement profiled sheets and fittings
Product specification and test methods

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

**Todd Alexander Kirk Edlin** 

Head of Group Product Compliance

Swisspearl Group AG Niederurnen, 10.10.2025 Joachim Ebenhoch

Global Head of Innovation Swisspearl Group AG

Niederurnen, 10.10.2025