

Declaration of Performance No. 057/DoP

In accordance with Regulation (EU) No 305/2011 of the European Parliament and of the Council laying down harmonised conditions for the marketing of construction products (CPR EU 305/2011)

1. Unique identification code of the product-type:

Fibre-cement slates

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Swisspearl TEC+ Slates

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Roofing (roof coverings)
Cladding
Internal and external wall finishes

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Swisspearl Group AG
Eternitstrasse 3
CH-8865 Niederurnen, Switzerland
Email: info@swisspearl.com

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

AVCP System 3



6a. Name and identification number of the notified body (in case of the declaration of performance concerning a construction product covered by a harmonised standard):

MA39-Prüf-, Überwachungs-, und Zertifizierungstelle Notified body No. 1139 VFA-Labors für Bautechnik Rinnböckstrasse 15 / 2 1110 Vienna, Austria

Notified Body performed the Initial Type Test according to EN 492.

IBS – Institut für Brandschutztechnik und Sicherheitsforschung GmbH Notified body No. 1322 Petzoldstrasse 45 4020 Linz, Austria

Notified Body performed reaction to fire and classification according to EN 13501-1.

6b. Name and identification number of the Technical Assessment Body (in case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued):

Not applicable

7. Declared performance:

Essential characteristics	Performance		Harmonised technical specification
Type of sheets	NT		
Mechanical resistance	h/mm	Bending moment	
	h ≤ 350	30 Nm/m	
	350 < h < 450		
	450 < h < 600		
	600 < h < 850	55 Nm/m	
Apparent density	Min. 1 600 kg/m ³		EN 492:2012+A2:2018 Fibre-cement profiled sheets and fittings - Product specification
External fire performance	Broof (deemed to satisfy)		
Reaction to fire	A2-s1, d0 (aluminium structure)		
Water impermeability	No water drops		
Dimensional variations			and test methods
Length, width	± 3 mm		and test methods
Thickness	+25% / -10% nominal value		
Release of dangerous substance	No performance determined		
Durability against warm water	R _L ≥ 0,75		
Durability against soak/dry	R _L ≥ 0,75		
Durability against freeze-thaw	R _L ≥ 0,75		
Durability against heat-rain	Pass		



8. Appropriate Technical Documentation and/or Specific Technical Documentation:

EN 492:2012+A2:2018
Fibre-cement profiled sheets and fittings
Product specification and test methods

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Esben Moos

Head of Product Compliance & Application Engineering

Swisspearl Group AG

Niederurnen, 01.05.2024

Joachim Ebenhoch

Head of Product Management & Development

Swisspearl Group AG

Niederurnen, 01.05.2024