

## Declaration of Performance

No. 001\_DoP\_2025-09-26

This Declaration of Performance (DoP) is in accordance with the Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonized conditions for the marketing of construction products (CPR EU 305/2011).

**1 Unique identification code of the product-type:**

PERMABASE DEK, 12.5mm thick  
Fibreglass-mesh reinforced cement flat sheets, type NT

**2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) of the CPR:**

Each product has a unique serial number consisting of the manufacturing plant identification code "BRO" followed by the manufacturing date and time code in the format "mm-dd-yy hh:mm"

**3 Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

Cement board for flat roofing applications

**4 Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5) of the CPR:**

UNIFIX INC, an affiliate of National Gypsum Company  
35 Unifix Street  
Bromont, Qc J2L 1N5  
Canada

**5 Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) of the CPR:**

Not applicable

**6 System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Annex V of the CPR:**

System 3

**7 Declared performances**

Essential characteristics	Performance	Harmonized technical specification
Reaction to Fire	Class A1	EN 12467:2012+A2:2018, EN 13501-1:2018 EN ISO 1182:2020, EN ISO 1716:2010
Release of dangerous substances	NPD	EN 12467:2012+A2:2018, EN ISO 16000-10

Mechanical resistance	12.5mm board: Category A, class 2 (Minimum 7 MPa), compliant	<b>EN 12467:2012+A1:2016</b>
Water impermeability	Category A, compliant	
Durability against warm water	Category A, $R_L > 0,75$ , compliant	
Durability against soak-dry	Category A, $R_L > 0,75$ , compliant	
Durability against freeze-thaw	Category A, $R_L > 0,75$ , compliant	
Durability against heat-rain	Category A, compliant	

The performance of the products identified in point 1 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

<b>Name and function</b>	Tony Fuller, Director-Technical & Product Development
<b>Place and date of issue</b>	Charlotte, NC (USA) September 26 2025
<b>Signature</b>	